

Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
1103	Ledfire LED Lite Emergency Light	9336462011034	4	0.00 Kg / 0.00 Kg

Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickle Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1925
Power Consumption	1.6W	Battery Capacity	850mAH
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	N/ A	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	C0:D16 C90:D16	Charger Type	Trickle
Wiring	2 Pin Flex and Plug	Normal charge current	0mA
Mounting Type	Recessed Mounting	Trickle charge current	43mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	1927	Charger Operation	Continuous
Class	2		

Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS Plastic Body	N/ A	High Temperature PBT	N/ A	70-120mm	0.900Kg	235mm	35mm	40mm	220mm

Spacing Table

Mounting Height	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
D16	12.1	12.6	13.0	13.3	13.6	13.9	14.1	14.6	14.6	14.6	14.4	13.8	12.9	11.5	N/ A	N/ A

Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Temperature and Duration	Light Lab International	LL0929604T	24/11/2009
Emergency Classification	Light Lab International	LL13206	24/11/2009

Accessories and Spare Parts

Model	Description	Model	Description
1925	Replacement battery for Ledfire LED Lite	1927	Replacement dish/ Lamp for LED Ledfire