

## Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
1612	Ledfire Surface Mount LED Emergency Light	9336462016121	4	0.00 Kg / 0.00 Kg
1613	Ledfire Surface Mount LED DALI Emergency Light	9336462016138	4	0.00 Kg / 0.00 Kg

## Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1919
Power Consumption	1.8	Battery Capacity	2100mAH
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	N/ A	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	C0:D40 C90:D40	Charger Type	Trickle
Wiring	3 x 6mm Terminals	Normal charge current	0mA
Mounting Type	Roof Mounted	Trickle charge current	120mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	N/ A	Charger Operation	Continuous

## Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
White Powder Coated Steel	N/ A	N/ A	N/ A	N/ A	1.500Kg	250mm	60mm	250mm	220mm

Spacing Table

Mounting Height	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
D40	16.7	17.4	18.0	18.6	19.1	19.6	20.1	20.8	21.3	22.1	22.7	23.0	23.1	23.1	19.4	N/ A

## Accessories and Spare Parts

Model	Description	Model	Description
1919	Replacement Battery 2100mAH NIMH	1913	Mercury Rod Mounting Bracket
1915	Mercury Cantilever Mounting bracket		