

## Ordering Information

Model	Description	Product Number	Outer Carton Quantity
1670	Ledfire LED	9336462016701	4
1672	Ledfire LED DALI	9336462016725	4

## Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1929
Power Consumption	1.7W	Battery Capacity	1200mAH
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	N/ A	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	C0:D25 C90:D25	Charger Type	Trickle
Wiring	2 Pin Flex and Plug	Normal charge current	0mA
Mounting Type	Recessed Mounting	Trickle charge current	60mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	1927	Charger Operation	Continuous

## Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS	ABS	High Temperature PBT	N/ A	70-120mm	0.500Kg	235mm	35mm	40mm	220mm

Spacing Table

Mounting Height	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
D25	14.2	14.7	15.3	15.7	16.1	16.5	16.9	17.3	17.7	18.1	18.3	18.2	17.9	17.3	7.7	N/ A

## Accessories and Spare Parts

Model	Description	Model	Description
1927	Replacement dish/ Lamp for LED Ledfire	1929	Replacement Battery 1200mAH 4.8V