

Ordering Information

Model	Description	Product Number	Outer Carton Quantity
1671	Ledfire LED PLUS	9336462016718	4
1673	Ledfire LED DALI PLUS	9336462016732	4

Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1926
Power Consumption	1.8	Battery Capacity	2100mAH
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	N/ A	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	C0:D40 C90:D40	Charger Type	Trickle
Wiring	5 Pin DALI Flex and Plug	Normal charge current	0mA
Mounting Type	Recessed Mounting	Trickle charge current	105mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	1928	Charger Operation	Continuous

Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS Plastic Body	N/ A	High Temperature PBT	N/ A	70-120mm	0.000Kg	235mm	35mm	40mm	220mm

Spacing Table

Mounting Height	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
D40	16.7	17.4	18.0	18.6	19.1	19.6	20.1	20.8	21.3	22.1	22.7	23.0	23.1	23.1	19.4	N/ A

Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Temperature and Duration	Light Lab International	LL0917505T	14/07/2009
Emergency Classification	Light Lab International	LL12905	15/07/2009

Accessories and Spare Parts

Model	Description	Model	Description
1926	Replacement battery for ledfire plus	1928	Replacement dish/ Lamp for LED Ledfire PLUS