

Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
2620	Razor 24m Exit Sign	9336462026205	4	0.00 Kg / 0.00 Kg
2621	Razor 24m [NZ] Exit Sign	9336462026212	4	0.00 Kg / 0.00 Kg
2625	Razor 24m DALI Exit Sign	9336462026251	4	0.00 Kg / 0.00 Kg
2626	Razor 24m DALI [NZ] Exit Sign	9336462026267	4	0.00 Kg / 0.00 Kg

Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1916
Power Consumption	2.3W	Battery Capacity	1200mAH
Operating Frequency	>40khz	Battery Voltage	3.6V
Viewing Distance	24M	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	N/ A	Charger Type	Trickle
Wiring	5 Pin DALI Flex and Plug	Normal charge current	0mA
Mounting Type	Recessed Mounting	Trickle charge current	60mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	2951	Charger Operation	Continuous
IP Rating	IP20		
Class	2		

Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS Plastic Body	N/ A	Acrylic	PVC	75mm x 325	1.286Kg	348mm	86mm	95mm	0mm

Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Temperature and Duration	Light Lab International	LL0735604T	27/12/2007
Radio Interference	Light Lab International	LL0800901E	16/01/2008
Luminance and Colour	Light Lab International Pty Ltd	LL13237	25/11/2009

Accessories and Spare Parts

Model	Description	Model	Description
1913	Mercury Rod Mounting Bracket	1915	Mercury Cantilever Mounting bracket
2930	Razor 24m SM KIT	1916	Razor Battery 1200mAH 3.6V
2951	Razor 24M Replacement Lamp		