

## Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
2630	Razor 32m Led Exit Sign	9336462026304	4	0.00 Kg / 0.00 Kg
2635	Razor 32m DALI LED exit sign	9336462026359	4	0.00 Kg / 0.00 Kg

## Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1926
Power Consumption	5.4W	Battery Capacity	2100mAh
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	32M	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	N/ A	Charger Type	Trickle
Wiring	2 Pin Flex and Plug	Normal charge current	0mA
Mounting Type	Recessed/ Surface	Trickle charge current	120mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	2952	Charger Operation	Continuous
IP Rating	IP20		
Class	2		

## Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS Plastic Body	N/ A	Acrylic	PVC	75mm x 425	0.000Kg	448mm	86mm	95mm	0mm

## Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Temperature and Duration	Light Lab International Pty Ltd	LL0929603T	25/11/2009
Luminance and Colour	Light Lab International Pty Ltd	LL13243	25/11/2009

## Accessories and Spare Parts

Model	Description	Model	Description
1926	Replacement battery for ledfire plus	1913	Mercury Rod Mounting Bracket
2952	Razor 32M replacement Decal/ Lamp [For AU Market]		