

Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
2650	Razor Slide Exit Sign	9336462026502	4	0.00 Kg / 0.00 Kg
2651	Razor Slide [NZ] Exit Sign	9336462026519	4	0.00 Kg / 0.00 Kg
2655	Razor Slide DALI Exit sign	9336462026557	4	0.00 Kg / 0.00 Kg
2656	Razor Slide DALI [NZ] Exit Sign	9336462026564	4	0.00 Kg / 0.00 Kg

Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1916
Power Consumption	2.3W	Battery Capacity	1200mAH
Operating Frequency	>40khz	Battery Voltage	3.6V
Viewing Distance	24M	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	N/ A	Charger Type	Trickle
Wiring	Hardwired	Normal charge current	0mA
Mounting Type	Surface Mounted	Trickle charge current	60mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	2954	Charger Operation	Continuous

Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
ABS Plastic Body	N/ A	Acrylic	PVC	N/ A	1.384Kg	380mm	245mm	70mm	160mm

Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Radio Interference	Light Lab International	LL0800901E	16/01/2008
Temperature and Duration	Light Lab International	LL0909604T	13/05/2009
Luminance and Colour	Light Lab International	LL12796	28/05/2009

Accessories and Spare Parts

Model	Description	Model	Description
1913	Mercury Rod Mounting Bracket	1915	Mercury Cantilever Mounting bracket
1916	Razor Battery 1200mAH 3.6V	2951	Razor 24M Replacement Lamp