

Ordering Information

Model	Description	Product Number	Outer Carton Quantity	Weight (Net/ Gross)
3625	Mercury WP (LSS) Exit sign	9336462036259	4	0.00 Kg / 0.00 Kg
3630	Mercury WP DALI (LSS) Exit sign	9336462036303	4	0.00 Kg / 0.00 Kg
3635	Mercury WP (LDS)	9336462036358	4	0.00 Kg / 0.00 Kg
3640	Mercury WP DALI (LDS)	9336462036402	4	0.00 Kg / 0.00 Kg
3645	Mercury WP (RSS)	9336462036457	4	0.00 Kg / 0.00 Kg
3650	Mercury WP DALI (RSS)	9336462036501	4	0.00 Kg / 0.00 Kg
3665	Mercury WP (XSS)	9336462036655	4	0.00 Kg / 0.00 Kg
3670	Mercury WP DALI (XSS)	9336462036709	4	0.00 Kg / 0.00 Kg

Operational Information

General		Battery	
Operational Voltage (V)	220-240V	Battery Type	High Temperature Nickel Metal Hydride
Operational Frequency (Hz)	50/60	Battery Code	1929
Power Consumption	4.3W	Battery Capacity	2100mAH
Operating Frequency	>40khz	Battery Voltage	4.8V
Viewing Distance	24M	Discharge Rating	2 Hours
Max. Ambient Temperature	40°C	Charger	
Photometric Classification	C0:D4 C90:D4	Charger Type	Trickle
Wiring	3 x 6mm Terminals	Normal charge current	0mA
Mounting Type	Roof Mounted	Trickle charge current	120mA
Replacement Lamp	LED	Charging Time	16 Hours
Lamp Re-Order Code	3907	Charger Operation	Continuous

Construction and Dimensions

Body	Gear Tray	Diffuser	Lens	Cut Out	Weight	Length	Heights	Width	Fixing Centres
PC Plastic Body	Steel	PC	PC	N/ A	1.200Kg	350mm	205mm	115mm	240mm

Spacing Table

Mounting Height	2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
D4	7.2	7.3	7.3	7.3	7.3	7.2	6.9	6.5	5.8	3.1	N/ A	N/ A	N/ A	N/ A	N/ A	N/ A

Compliance

Test Type	Laboratory	Test Report Number	Date of Issue
Temperature and Duration	LightLab Pty Ltd	LL0835102T	16/12/2008
Luminance and Colour	LightLab Pty Ltd	LL12513	03/02/2009
Emergency Classification	LightLab Pty Ltd	LL12515	03/02/2009

Accessories and Spare Parts

Model	Description	Model	Description
1926	Replacement battery for ledfire plus	1913	Mercury Rod Mounting Bracket